



# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 08/09/2016

Date of Issue: 08/09/2016

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Graphite Products with Metallic Additives

#### 1.2. Intended Use of the Product

Electrical component

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

St. Mary's Carbon

259 Eberl St.

St. Mary's PA, 15857

814-781-7333

[www.stmaryscarbon.com](http://www.stmaryscarbon.com)

#### 1.4. Emergency Telephone Number

**Emergency Number** : 814-781-7333 (Hours of Operation: 7:30 a.m.- 4:00 p.m. M-F)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Not classified

#### 2.2. Label Elements

##### GHS-US/CA Labeling

No labeling applicable

#### 2.3. Other Hazards

This product is physiologically inert in its massive form. However, user-generated dust and/or fumes may pose a physiological hazard if inhaled or ingested. Avoid inhalation of metal dusts and fumes. May cause an influenza-like illness. Avoid skin and eye contact with dusts to prevent mechanical irritation. User-generated dust is easily ignited and difficult to extinguish.

#### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Copper	(CAS No) 7440-50-8	55 - 80	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Graphite	(CAS No) 7782-42-5	12 - 40	Comb. Dust
Lead	(CAS No) 7439-92-1	2 - 7	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 1B, H350 Repr. 1A, H360 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Molybdenum(IV) sulfide	(CAS No) 1317-33-5	2 - 6	Acute Tox. 4 (Inhalation:dust,mist), H332
Quartz	(CAS No) 14808-60-7	< 1	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372

# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** Not expected to present a significant inhalation hazard under anticipated conditions of normal use. When symptoms occur: go into open air and ventilate suspected area.

**Skin Contact:** Gently wash with plenty of soap and water. Obtain medical attention if irritation develops or persists. Cool skin rapidly with cold water after contact with molten product.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention. Removal of solidified molten material from the eyes requires medical assistance.

**Ingestion:** Rinse mouth. Do not induce vomiting. Obtain medical attention.

#### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Under normal conditions of use not expected to present a significant hazard. Under milling, or physical alteration metal dusts may be produced that cause irritation of the respiratory tract, skin, and may be harmful. Molten material may release toxic, and irritating fumes.

**Inhalation:** During processing, the most significant route of exposure is by the inhalation (breathing) of fumes. If fumes are inhaled, they can cause a condition commonly known as metal fume fever with symptoms which resemble influenza; Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea and prostration may also occur.

**Skin Contact:** Risk of thermal burns on contact with molten product. Dust from physical alteration of this product causes skin irritation.

**Eye Contact:** During metal processing. Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** For particulates and dust: Lead: Exposure can result in lassitude (weakness, exhaustion), insomnia; facial pallor; anorexia, weight loss, malnutrition; constipation, abdominal pain, colic; anemia; gingival lead line; tremor; encephalopathy; kidney disease; hypertension. Molybdenum: Chronic exposure to molybdenum compounds is suspected of causing cancer. Compounds are also known to cause irritation to the skin, eyes, and respiratory tract. Prolonged or repeated exposure of silica in its respirable form can cause lung disease, however the silica in this product is not airborne and therefore not bioavailable. Limited and contradictory evidence suggest that silica may be a carcinogen when inhaled for many years (IARC).

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product SDS at hand.

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Use Class D extinguishing agents on dusts, fines or molten metal. Use coarse water spray on chips and turnings.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire. Do not use water when molten material is involved, contact of hot product with water will result in a violent expansion as the water turns to steam causing explosion with massive force.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Dust, chips, or ribbons can be ignited more easily, by an ignition source, by improper machining, or by spontaneous combustion if finely divided and damp.

**Explosion Hazard:** Product itself is not explosive but if dust is generated, dust clouds suspended in air can be explosive.

**Reactivity:** Dust and other forms of product formed from processing might react with water producing a flammable/explosive environment, especially in confined spaces. Molten material will react violently with water.

# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. Appropriate self-contained breathing apparatus may be required.

**Hazardous Combustion Products:** Metal oxides.

**Other Information:** Risk of dust explosion.

### Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood. Avoid generating dust. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate area.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. Avoid generation of dust during clean-up of spills. If metal is in molten form allow to cool and collect as a solid. If metal is in solid form collect for remelting purposes.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Contact competent authorities after a spill. For particulates and dust: Use explosion proof vacuum during cleanup, with appropriate filter. Do not mix with other materials. Vacuum clean-up is preferred. If sweeping is required use a dust suppressant. Use only non-sparking tools.

### 6.4. Reference to Other Sections

See Section 8 for advice on personal protective equipment and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Dust particles generated from processing may cause an allergic reaction in sensitive individuals. Dust generated from processing may present a dust explosion hazard. Chips, fines, and dust can react with water forming explosive/flammable hydrogen gas. Molten material may react violently with water forming explosive or flammable reactions. A thermite reaction may also occur under certain conditions.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Handle in a manner to prevent any potential exposure. Follow appropriate administrative policies and procedures. Do not breathe dust. Avoid creating or spreading dust. Keep away from heat, sparks, open flames, hot surfaces. – No smoking.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Avoid creating or spreading dust. Use explosion-proof electrical, ventilating, and lighting equipment. Proper grounding procedures to avoid static electricity should be followed.

**Storage Conditions:** Keep container closed when not in use. Store in a cool, dry place. Keep away from moisture, extremely high or low temperatures, ignition sources, and incompatible materials.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers. When molten: water.

### 7.3. Specific End Use(s)

Electrical component

# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

<b>Copper (7440-50-8)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (dust and mist) 0.1 mg/m <sup>3</sup> (fume)
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (dust, fume and mist)
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (dust and mist) 0.2 mg/m <sup>3</sup> (fume)
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	0.6 mg/m <sup>3</sup> (fume) 2 mg/m <sup>3</sup> (dust and mist)
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (dust and mist) 0.6 mg/m <sup>3</sup> (fume)
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>Prince Edward Island</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>Saskatchewan</b>	OEL STEL (mg/m <sup>3</sup> )	0.6 mg/m <sup>3</sup> (fume) 3 mg/m <sup>3</sup> (dust and mist)
<b>Saskatchewan</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 2 mg/m <sup>3</sup> (dust and mist)
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>Lead (7439-92-1)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>USA ACGIH</b>	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
<b>USA ACGIH</b>	Biological Exposure Indices (BEI)	30 µg/100ml (Medium: blood - Time: not critical - Parameter: Lead (Note: Women of child bearing potential, whose blood Pb exceeds 10 µg/dL, are at risk of delivering a child with a blood Pb over the current Centers for Disease Control guideline of 10 µg/dL. If the blood Pb of such children remains elevated, they may be at increased

# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		risk of cognitive deficits. The blood Pb of these children should be closely monitored and appropriate steps should be taken to minimize the child's exposure to environmental lead.)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 µg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.050 mg/m <sup>3</sup>
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	0.45 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	0.15 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	0.15 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (designated substances regulation) 0.05 mg/m <sup>3</sup> (applies to workplaces to which the designated substances regulation does not apply)
<b>Prince Edward Island</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>Saskatchewan</b>	OEL STEL (mg/m <sup>3</sup> )	0.15 mg/m <sup>3</sup>
<b>Saskatchewan</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	0.45 mg/m <sup>3</sup> (dust and fume)
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	0.15 mg/m <sup>3</sup> (dust and fume)
<b>Molybdenum(IV) sulfide (1317-33-5)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable fraction); 3mg/m <sup>3</sup> TWA (respirable fraction)(listed under Molybdenum)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)(listed under Molybdenum insoluble compounds)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup> (Listed under Molybdenum)
<b>Graphite (7782-42-5)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (all forms except graphite fibers-respirable fraction)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (synthetic-total dust) 5 mg/m <sup>3</sup> (synthetic-respirable fraction)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup> (natural-respirable dust)
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	1250 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (all forms except Graphite fibres-respirable)
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (all forms except Graphite fibres-respirable)
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (all forms except Graphite fibers-respirable fraction)
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (all forms except graphite fibres)
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (all forms except Graphite fibers-respirable fraction)
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (all forms except Graphite fibres-respirable fraction)
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (synthetic-respirable mass) 10 mg/m <sup>3</sup> (synthetic, total mass)
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup> (natural-respirable fraction)
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (natural-respirable fraction)

# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).


Ontario	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (except Graphite fibres-respirable)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (all forms except Graphite fibers-respirable fraction)
Québec	VEMP (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica, except Graphite fibres-respirable dust)
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup> (natural, except Graphite fibres-respirable fraction)
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (natural, except Graphite fibres-respirable fraction)
Yukon	OEL TWA (mg/m <sup>3</sup> )	20 mppcf 30 mppcf (synthetic) 10 mg/m <sup>3</sup> (synthetic)

<b>Quartz (14808-60-7)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (STEL) (mg/m <sup>3</sup> )	250 mppcf/%SiO <sub>2</sub> +5, 10mg/m <sup>3</sup> /%SiO <sub>2</sub> +2
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable dust)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup> (respirable dust)
Alberta	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate)
British Columbia	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable)
Manitoba	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
Nunavut	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable mass) 0.3 mg/m <sup>3</sup> (total mass)
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)
Ontario	OEL TWA (mg/m <sup>3</sup> )	0.10 mg/m <sup>3</sup> (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
Québec	VEMP (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable dust)
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)
Yukon	OEL TWA (mg/m <sup>3</sup> )	300 particle/mL

## 8.2. Exposure Controls

**Appropriate Engineering Controls:** The following applies to the product if it is cut, sanded or altered in such a way that excessive and/or significant particulates and/or dusts may be generated: Provide adequate ventilation to minimize dust concentrations.

**Materials for Protective Clothing:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. With molten material wear thermally protective clothing.

**Hand Protection:** Wear protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Physical State</b>	: Solid
<b>Appearance</b>	: Copper colored
<b>Odor</b>	: None
<b>Odor Threshold</b>	: Not available
<b>pH</b>	: Not available
<b>Evaporation Rate</b>	: Not available
<b>Melting Point</b>	: Not available
<b>Freezing Point</b>	: Not available
<b>Boiling Point</b>	: Not available
<b>Flash Point</b>	: Not available
<b>Auto-ignition Temperature</b>	: Not available
<b>Decomposition Temperature</b>	: Not available
<b>Flammability (solid, gas)</b>	: Not available
<b>Lower Flammable Limit</b>	: Not available
<b>Upper Flammable Limit</b>	: Not available
<b>Vapor Pressure</b>	: Not available
<b>Relative Vapor Density at 20°C</b>	: Not available
<b>Relative Density</b>	: 3 - 5
<b>Specific Gravity</b>	: Not available
<b>Solubility</b>	: Not available
<b>Partition Coefficient: N-Octanol/Water</b>	: Not available
<b>Viscosity</b>	: Not available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Dust and other forms of product formed from processing might react with water producing a flammable/explosive environment, especially in confined spaces. Molten material will react violently with water.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous reactions will not occur under normal conditions.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources. Dust accumulation (to minimize explosion hazard).
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. When molten: water.
- 10.6. Hazardous Decomposition Products:** None known.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Oral: Not classified.

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

**Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified.

**Reproductive Toxicity:** Not classified.

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** During processing, the most significant route of exposure is by the inhalation (breathing) of fumes. If fumes are inhaled, they can cause a condition commonly known as metal fume fever with symptoms which resemble influenza; Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the

# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea and prostration may also occur.

**Symptoms/Injuries After Skin Contact:** Risk of thermal burns on contact with molten product. Dust from physical alteration of this product causes skin irritation.

**Symptoms/Injuries After Eye Contact:** During metal processing. Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** For particulates and dust: Lead: Exposure can result in lassitude (weakness, exhaustion), insomnia; facial pallor; anorexia, weight loss, malnutrition; constipation, abdominal pain, colic; anemia; gingival lead line; tremor; encephalopathy; kidney disease; hypertension. Molybdenum: Chronic exposure to molybdenum compounds is suspected of causing cancer. Compounds are also known to cause irritation to the skin, eyes, and respiratory tract. Prolonged or repeated exposure of silica in its respirable form can cause lung disease, however the silica in this product is not airborne and therefore not bioavailable. Limited and contradictory evidence suggest that silica may be a carcinogen when inhaled for many years (IARC).

### 11.2. Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

<b>Lead (7439-92-1)</b>	
ATE US/CA (oral)	500.00 mg/kg body weight
ATE US/CA (dust, mist)	1.50 mg/l/4h
<b>Molybdenum(IV) sulfide (1317-33-5)</b>	
LC50 Inhalation Rat	> 2820 mg/m <sup>3</sup> (Exposure time: 4 h)
<b>Quartz (14808-60-7)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
<b>Lead (7439-92-1)</b>	
IARC Group	2A
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
<b>Quartz (14808-60-7)</b>	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity No additional information available

<b>Copper (7440-50-8)</b>	
LC50 Fish 1	0.0068 - 0.0156 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 1	0.0426 (0.0426 - 0.0535) mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
LC50 Fish 2	< 0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	0.031 (0.031 - 0.054) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])
<b>Lead (7439-92-1)</b>	
LC50 Fish 1	0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 1	600 µg/l (Exposure time: 48 h - Species: water flea)
LC50 Fish 2	1.17 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

### 12.2. Persistence and Degradability

<b>Copper (7440-50-8)</b>	
Persistence and Degradability	Not readily biodegradable.



# SDS 8

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**12.3. Bioaccumulative Potential** Not available

**12.4. Mobility in Soil** Not available

**12.5. Other Adverse Effects** Not available

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations

**Ecology - Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

**14.1. In Accordance with DOT** Not regulated for transport

**14.2. In Accordance with IMDG** Not regulated for transport

**14.3. In Accordance with IATA** Not regulated for transport

**14.4. In Accordance with TDG** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

#### Copper (7440-50-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

<b>SARA Section 313 - Emission Reporting</b>	1.0 %
--	-------

#### Lead (7439-92-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

<b>SARA Section 313 - Emission Reporting</b>	0.1 %
--	-------

#### Molybdenum(IV) sulfide (1317-33-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Graphite (7782-42-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. US State Regulations

#### Lead (7439-92-1)

<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
--	--

<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
--	---

<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Female</b>	WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm.
--	--

<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Male</b>	WARNING: This product contains chemicals known to the State of California to cause (Male) reproductive harm.
--	--

#### Quartz (14808-60-7)

<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
--	--

#### Copper (7440-50-8)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List

# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Lead (7439-92-1)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Molybdenum(IV) sulfide (1317-33-5)</b>
U.S. - Massachusetts - Right To Know List
<b>Graphite (7782-42-5)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Quartz (14808-60-7)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

### 15.3. Canadian Regulations

<b>Copper (7440-50-8)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Lead (7439-92-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Molybdenum(IV) sulfide (1317-33-5)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Graphite (7782-42-5)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Quartz (14808-60-7)</b>
Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

<b>Revision Date</b>	: 08/09/2016
<b>Other Information</b>	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR).

### GHS Full Text Phrases:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Comb. Dust	May form combustible dust concentrations in air
Repr. 1A	Reproductive toxicity Category 1A
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H302	Harmful if swallowed
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H360	May damage fertility or the unborn child


# SDS 8

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

- NFPA Health Hazard** : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.
- NFPA Fire Hazard** : 1 - Must be preheated before ignition can occur.
- NFPA Reactivity Hazard** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

- Health** : 0 Minimal Hazard - No significant risk to health
- Flammability** : 1 Slight Hazard
- Physical** : 0 Minimal Hazard

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (US, Can)